

SUPREME Chlorinated Rubber Traffic Paint

Safety Data Sheet

Issue Date: 16-Dec-2019

Revision Date: 18-Mar-2025

Version 2

1. IDENTIFICATION

Product identifier

Product Name SUPREME Chlorinated Rubber Traffic Paint

Other means of identification

SDS # USS-005

UN/ID No UN1307

Recommended use of the chemical and restrictions on use

Recommended Use Traffic Paint

Details of the supplier of the safety data sheet

Supplier Address

US Specialty Coatings
1000 McFarland 400 Blvd
Alpharetta, GA 30004 USA

Emergency telephone number

Company Phone Number Phone: 770-813-0008
800-728-7972
Fax: 770-813-0470

Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Physical state Liquid

Classification

Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Flammable liquids	Category 3

Signal Word

Warning

Hazard statements

Harmful in contact with skin
Harmful if inhaled
Causes skin irritation
Suspected of damaging fertility or the unborn child
Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Use explosion-proof equipment

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
Call a poison center or doctor/physician if you feel unwell
If skin irritation occurs: Get medical advice/attention
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a poison center or doctor/physician if you feel unwell
In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Xylene	1330-20-7	60-70
Titanium(IV) Oxide	13463-67-7	5-15
Talc	14807-96-6	1-5
Bentonite Clay	1302-78-9	1-5
Barium Sulfate	7727-43-7	1-5
Amorphous silica (glass)	7631-86-9	0-1
Toluene	108-88-3	0-1
Aluminum Hydroxide	21645-51-2	0-1
Crystalline silica	14808-60-7	0-1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures****General Advice**

Provide this SDS to medical personnel for treatment.

Eye Contact

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin Contact	Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Call a poison center or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Call a poison center or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms	Harmful in contact with skin. Harmful if inhaled. May be harmful if swallowed. Causes skin irritation.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media	Not determined.
---------------------------------------	-----------------

Specific Hazards Arising from the Chemical

Flammable liquid and vapor.

Hazardous combustion products	Smoke, fumes or vapors, and oxides of carbon.
--------------------------------------	---

Explosion Data

Sensitivity to Static Discharge	Take precautionary measures against static discharge.
--	---

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions	Use personal protective equipment as required.
-----------------------------	--

Environmental precautions

Environmental precautions	See Section 12 for additional Ecological Information.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
--------------------------------	---

Methods for Clean-Up	Keep in suitable, closed containers for disposal.
-----------------------------	---

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Use explosion proof equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Incompatible Materials

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Titanium(IV) Oxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Bentonite Clay 1302-78-9	TWA: 1 mg/m ³ respirable particulate matter	-	-
Barium Sulfate 7727-43-7	TWA: 5 mg/m ³ inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Amorphous silica (glass) 7631-86-9	-	TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO ₂) mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Aluminum Hydroxide 21645-51-2	TWA: 1 mg/m ³ respirable particulate matter	-	-
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Crystalline silica	TWA: 0.025 mg/m ³ respirable	TWA: 50 µg/m ³ TWA: 50 µg/m ³	IDLH: 50 mg/m ³ respirable dust

14808-60-7	particulate matter	excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	TWA: 0.05 mg/m ³ respirable dust
------------	--------------------	--	---

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear eye/face protection. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Wear protective gloves and protective clothing. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Not determined
Appearance	Not determined	Odor Threshold	Not determined
Color	Not determined		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	Not determined		
Melting point / freezing point	Not determined		
Boiling point / boiling range	137 °C / 279 °F	(Xylene)	
Flash point	25 °C / 77 °F		
Evaporation Rate	Not determined		
Flammability (Solid, Gas)	Liquid - Not Applicable		
Flammability Limit in Air			
Upper flammability or explosive limits	Not determined		
Lower flammability or explosive limits	Not determined		
Vapor Pressure	Not determined		
Vapor Density	Not determined		
Relative Density	Not determined		
Water Solubility	Not determined		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Autoignition temperature	Not determined		
Decomposition temperature	Not determined		
Kinematic viscosity	Not determined		
Dynamic Viscosity	Not determined		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	Harmful in contact with skin.
Inhalation	Harmful if inhaled.
Ingestion	May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Water 7732-18-5 Mar-2025	> 90 mL/kg (Rat)	-	-
Titanium(IV) Oxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Bis(2-ethylhexyl) adipate 103-23-1	= 5600 mg/kg (Rat)	= 8410 mg/kg (Rabbit)	-
Bentonite Clay 1302-78-9	> 5000 mg/kg (Rat)	-	-
Barium Sulfate 7727-43-7	= 307000 mg/kg (Rat)	-	-
Amorphous silica (glass) 7631-86-9	= 7900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Aluminum Hydroxide 21645-51-2	> 5000 mg/kg (Rat)	-	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Please see section 4 of this SDS for symptoms.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Carcinogenicity Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Silica (quartz) is a possible carcinogen when it appears as a respirable dust. Group 3 IARC components are "not classifiable as human carcinogens".

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		
Titanium(IV) Oxide 13463-67-7		Group 2B		X
Bis(2-ethylhexyl) adipate 103-23-1		Group 3		
Amorphous silica (glass) 7631-86-9		Group 3	Known	X
Toluene 108-88-3		Group 3		

Legend

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT - repeated exposure Respirable crystalline silica causes damage to organs (lung effects, immune system effects, and kidney effects) through prolonged or repeated exposure.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Oral LD50 4,159.53 mg/kg

Dermal LD50 1,482.50 mg/kg

ATEmix (inhalation-dust/mist) 1.87 mg/L

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Xylene 1330-20-7		13.1 - 16.5: 96 h <i>Lepomis macrochirus</i> mg/L LC50 flow-through 19: 96 h <i>Lepomis macrochirus</i> mg/L LC50 23.53 - 29.97: 96 h <i>Pimephales promelas</i> mg/L LC50 static 7.711 - 9.591: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 780: 96 h <i>Cyprinus carpio</i> mg/L LC50 semi-static 2.661 - 4.093: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 30.26 - 40.75: 96 h <i>Poecilia reticulata</i> mg/L LC50 static 13.5 - 17.3: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 13.4: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 780: 96 h <i>Cyprinus carpio</i> mg/L LC50	0.6: 48 h <i>Gammarus lacustris</i> mg/L LC50 3.82: 48 h water flea mg/L EC50

Talc 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
Bis(2-ethylhexyl) adipate 103-23-1	500: 72 h Desmodesmus subspicatus mg/L EC50	0.48 - 0.85: 96 h Pimephales promelas mg/L LC50 static 0.48 - 0.85: 96 h Lepomis macrochirus mg/L LC50 static 54 - 150: 96 h Salmo gairdneri mg/L LC50 static 0.48 - 0.85: 96 h Oncorhynchus mykiss mg/L LC50 static	1.6: 48 h Daphnia magna mg/L EC50
Bentonite Clay 1302-78-9		19000: 96 h Oncorhynchus mykiss mg/L LC50 static 8.0 - 19.0: 96 h Salmo gairdneri g/L LC50	
Amorphous silica (glass) 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
Toluene 108-88-3	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	12.6: 96 h Pimephales promelas mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static	11.5: 48 h Daphnia magna mg/L EC50 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Xylene 1330-20-7	3.15
Toluene 108-88-3	2.7

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Toluene 108-88-3	Toxic Ignitable

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1307
 Proper Shipping Name Xylenes
 Hazard class 3
 Packing Group III

IATA

UN number UN1307
 Proper Shipping Name Xylenes
 Transport hazard class(es) 3
 Packing Group III

IMDG

UN number UN1307
 Proper Shipping Name Xylenes
 Transport hazard class(es) 3
 Packing Group III

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Xylene	X	ACTIVE	X	X	X	X	X	X	X
Titanium(IV) Oxide	X	ACTIVE	X	X	X	X	X	X	X
Talc	X	ACTIVE	X	X	X	X	X	X	X
Bis(2-ethylhexyl) adipate	X	ACTIVE	X	X	X	X	X	X	X
Bentonite Clay	X	ACTIVE	X	X		X	X	X	X
Barium Sulfate	X	ACTIVE	X	X	X	X	X	X	X
Dolomite	X	ACTIVE	X	X		X	X	X	X
Amorphous silica (glass)	X	ACTIVE	X	X	X	X	X	X	X
Aluminum Hydroxide	X	ACTIVE	X	X	X	X	X	X	X
Toluene	X	ACTIVE	X	X	X	X	X	X	X
Crystalline silica	X	ACTIVE	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Toluene 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	50-60	1.0
Barium Sulfate - 7727-43-7	7727-43-7	1-5	1.0
Toluene - 108-88-3	108-88-3	0-1	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb			X
Toluene	1000 lb	X	X	X

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Titanium(IV) Oxide - 13463-67-7	Carcinogen
Amorphous silica (glass) - 7631-86-9	Carcinogen
Toluene - 108-88-3	Developmental
Crystalline silica - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	X
Titanium(IV) Oxide 13463-67-7	X	X	X
Talc 14807-96-6	X	X	X
Bis(2-ethylhexyl) adipate 103-23-1	X	X	X
Barium Sulfate 7727-43-7	X	X	X
Amorphous silica (glass) 7631-86-9		X	X
Toluene 108-88-3	X	X	X
Crystalline silica 14808-60-7	X	X	X

16. OTHER INFORMATION**NFPA****Health Hazards**

Not determined

Flammability

Not determined

Instability

Not determined

Special Hazards

Not determined

HMIS**Health Hazards**

Not determined

Flammability

Not determined

Physical hazards

Not determined

Personal Protection

Not determined

Issue Date:

16-Dec-2019

Revision Date:

18-Mar-2025

Revision Note:

Regulatory update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet